

India's
leading
supplier



www.rushitechniques.com

**First Time in India Online tension
increase or decrease** smart Function in all model

Premium Model

Conductor capacity : 0.40 mm to 2.00 mm.

Maximum line speed : 65 mtr/Min.

Maximum Spindle speed : 2500 rpm.

Maximum tape size : 320mm outside diameter 40mm height
up to 50mm bore and custom size.

Taping spindle through bore : 12mm diameter conception.

Take off Rill Capacity : Torque Controlled up to 80 Kg.

Electrical supply : 440 volt. 3 phase 50 hertz 2 HP AC inverter each line.

Machine weight : 600 kg.

One year Warranty *



Jumbo Super Delux

Conductor capacity : 1.50 mm to 4.00mm.

Maximum line speed : 40 mtr/Min.

Maximum Spindle speed : 1800 rpm.

Maximum tape size : 320mm outside diameter 40mm height
up to 50mm bore and custom size.

Taping spindle through bore : 12mm diameter conception.

Take off Rill Capacity : Torque Controlled up to 100 Kg.

Electrical supply : 440 volt. 3 phase 50 hertz 3 HP AC inverter each line.

Machine weight : 1100 kg.

One year Warranty *

With torque motor

Mtr / Min. Indicator

Counter Indicator

Spindle rpm Indicator

Electro Magnetic Tension control System

With strobe light (for watch tap position)



Since:1996

RUSHI® **TECHNIQUES**

A Complete Solution of Winding Wire Machineries

Survey No. 204, Plot No. 4,
Veraval Main Road, Veraval (Shapar)
Dist. Rajkot - 360 024, Gujrat, India.

E-mail : rushitechniques@gmail.com
Web : www.rushitechniques.com
Mob. : 70690 53716, 99241 14185

An ISO 9001:2008 Certified Company



Winding Wire
A Complete Project

Since:1996

RUSHI[®]
TECHNIQUES

www.rushitechniques.com

Star Model

Conductor capacity : 0.40 mm to 2.00mm.

Maximum line speed : 48 mtr/Min.

Maximum Spindle speed : 2500 rpm.

Maximum tape size : 320mm OD 40mm height up to 50mm bore and custom size.

Taping spindle through bore : 12mm diameter conception.

Take off Rill Capacity : 40 Kg. Max.

Electrical supply : 440 volt. 3 phase 50 hertz 2 HP AC inverter each line.

Machine weight : 550 kg.



One year Warranty *



Standard Model

Conductor capacity : 0.40 mm to 2.00mm.

Maximum line speed : 48 mtr/Min.

Maximum Spindle speed : 2500 rpm.

Maximum tape size : 320mm OD 40mm height up to 50mm bore and custom size.

Taping spindle through bore : 12mm diameter conception.

Take off Rill Capacity : 40 Kg. Max.

Electrical supply : 440 volt. 3 phase 50 hertz 2 HP AC inverter each line.

Machine weight : 500 kg.

Counter Indicator
Mechanical Tension control System
With strobe light (for watch tap position)

One year Warranty *

Basic Model

Conductor capacity : 0.40 mm to 2.00 mm.

Maximum line speed : 45 mtr/min

Maximum Spindle speed : 2250 rpm.

Maximum tape size : 320mm OD 40mm height up to 50mm bore and custom size.

Taping spindle through bore : 10mm diameter conception.

Take off Rill Capacity : 40 Kg. max.

Electrical supply : 440 volt. 3 phase 50 hertz 2 HP AC inverter each line.

Machine weight : 375 kg.

Counter Indicator
Mechanical Tension control System



One year Warranty *

India's
leading
supplier



www.rushitechniques.com

First Time in India Online tension
increase or decrease smart Function in all model



Oven

Temperature capacity : 275°C Max.

Cabin Size : L-72" x W-44" x H-54"

Electrical Supply : 440V-50/60Hz

Power Consumption : 15KV.

Machine Weight : 1200 kg.

*Machines are also made as per Customers Requirement

One year Warranty *

Slitting Machine



One year Warranty *

Coiling Machine



One year Warranty *

* without bearings

Since:1996
RUSHI[®] TECHNIQUES

A Complete Solution of Winding Wire Machineries

Survey No. 204, Plot No. 4,
Veraval Main Road, Veraval (Shapar)
Dist. Rajkot - 360 024, Gujrat, India.

E-mail : rushitechniques@gmail.com
Web : www.rushitechniques.com
Mob. : 70690 53716, 99241 14185

An ISO 9001:2008 Certified Company



Winding Wire
A Complete Project